

# YL-32



## STANDARD DIE SETS

Size	Range (mm)	Length
<b>32-10</b>	10-13	55
<b>32-13</b>	13-16	55
<b>32-16</b>	16-19	55
<b>32-19</b>	19-22	55
<b>32-22</b>	22-26	55
<b>32-26</b>	26-30	55
<b>32-30</b>	30-34	75
<b>32-34</b>	34-39	75
<b>32-39</b>	39-45	75
<b>32-45</b>	45-52	90
<b>32-52</b>	52-57	90
<b>32-57</b>	57-64	90
<b>32-64</b>	64-69	100
<b>32-69</b>	69-74	100

## TECHNICAL SPECIFICATIONS

<b>Max hose size</b>	2" 4 SP
<b>Crimping force (kN):</b>	2200
<b>Max crimping Ø (mm):</b>	79
<b>Max opening (mm):</b>	die diameter + 32
<b>Standard motor:</b>	3,6kW 380V 3-ph
Different voltage versions available	
<b>Control</b>	Digital control
<b>Master dies opening / Length (mm):</b>	132/80
<b>Crimping range (mm):</b>	10 – 79
<b>Weight (kg)</b>	300 (including oil)
<b>Dimensions (LxWxH mm)</b>	600 x 480 x 1300
<b>Die sets</b>	Standard
10-13-16-19-22-26-30-34-39-45-52-57-64-69	
<b>Quick Change-set</b>	Standard
<b>Foot pedal</b>	Standard
<b>Stand for machine</b>	Standard